



ULTIMATE PLUS

up to 50,700 gal/day (192,000 l/day)

CUSTOM-MADE DECONTAMINATION SOLUTIONS



Configuration ULT3000 + EXT3000



Capacity: **Main skid: 790 gallons per hour (3,000 l/hour)**
Each add-on: 790 gallons per hour (3,000 l/hour)
 Possibility to connect 3 add-ons of 790 gal/hour
 Capacity up to 3,160 gal/h (12,000 lph)

Recommended daily operation: Up to **16 hours per day**
 Effluent: **Water-like**



Utilities: **Steam**
 No chilled water required



Treatment program: 176°F to 275°F (80°C to 135°C) for 1 minute (2 minutes as option)
 Decontamination: F₀ 25 (F₀ 50 as an option)



Height: **93"** (2,350 mm)
 Layout: Main skid ULT3000: **27" x 98"** (1,700 x 2,480 mm)
 Extension EXT3000 : **37" x 100"** (940 x 2,530 mm)

Main Features

- Modular system
- Capacity upgrade easy to implement in connecting 790-gal/hour (3,000-lph) modules
- Really compact add-ons
- Automatic operation controlled from the main skid. No automation study required when connecting add-ons.
- Possibility to double the pumping system for redundancy.

ULT+ MODEL

